

# QUOTATION

## Highseal Manufacturing Company

26 Hebden Road  
Scunthorpe  
North Lincs  
DN15 8DT

**Tel: 01724 859326**

**Fax: 01724 845576**

Quotation No : 36398  
Printed Date : 30-Jan-2026  
Representative :  
Customer : Retail  
Pricing Method : Manual


KAMIL STANIEE

Tel:  
Fax:

**Quotation Spec**  
Glazed / Supply Only

Quotation Reference  
**8 WEBSTER AVE**


<b>Elite 70 Ovolo Bay Layout</b>	<b>Specification</b>
----------------------------------	----------------------



Cill	C225 225mm Classic Nose Cill
Add-on (Left jamb)	No add-on
Add-on (Right jamb)	No add-on
Pole	B70 Bav Pole (Elite 70)
Colour	White
Sash colour	White
Addon colour	White
Cill colour	White
Viewed from	Viewed from outside
Reinforcing rule	Bav Reinforcing
Reinforcing type	Steel Reinforcing

Notes :

<b>1 Elite 70 Ovolo Casement</b>	<b>Bay 1 of 5</b>
<b>O/A Sizes 495mm x 1650mm (Style 8)</b>	<b>Specification</b>



Transom	B20/21 66mm T/Z Section
Sash (Head)	B35 75mm T Sash
Sash (Cill)	B35 75mm T Sash
Sash (Left jamb)	B35 75mm T Sash
Sash (Right jamb)	B35 75mm T Sash
Frame drip bar	No drip bar
Add-on (Head)	No add-on
Add-on (Cill)	No add-on
Add-on (Left jamb)	No add-on
Add-on (Right jamb)	No add-on
Ventilator (Head)	No ventilator
Ventilator (Sash)	5000 SIMON VENT
Ventilator (Glass)	No ventilator
Ventilator (Frame)	No ventilator
Colour	White
Sash colour	White
Handle	White Cranked Espag Handle
Casement locking	Maco MK3 Shootbolt Locking
Friction stay	Egress Stay
Viewed from	Viewed from outside
Open in/out	Open out
Reinforcing rule	Bav Reinforcing
Reinforcing type	Steel Reinforcing
Tran/Mull joints	Welded joint
Vector Excluder	Vector Excluder
<b>WER RATING</b>	<b>A RATED</b>

**Glazing Details & Apertures**

4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer      \*Argon Gas Filled \*


A1    A4


Notes :


<b>2</b>	Elite 70 Ovolo Casement	Bay 2 of 5
O/A Sizes 435mm x 1650mm (Style 2)		<b>Specification</b>
	Transom	B20/21 66mm T/Z Section
	Frame drip bar Add-on (Head) Add-on (Cill) Add-on (Left jamb) Add-on (Right jamb) Ventilator (Head) Ventilator (Glass) Ventilator (Frame) Colour Viewed from Reinforcing rule Reinforcing type Tran/Mull joints <b>WER RATING</b>	No drip bar No add-on No add-on No add-on No add-on No ventilator No ventilator No ventilator White Viewed from outside Bay Reinforcing Steel Reinforcing Welded joint <b>A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		


<b>3</b>	Elite 70 Ovolo Casement	Bay 3 of 5
O/A Sizes 435mm x 1650mm (Style 6)		<b>Specification</b>
	Transom	B20/21 66mm T/Z Section
	Sash (Head) Sash (Cill) Sash (Left jamb) Sash (Right jamb) Frame drip bar Add-on (Head) Add-on (Cill) Add-on (Left jamb) Add-on (Right jamb) Ventilator (Head) Ventilator (Sash) Ventilator (Glass) Ventilator (Frame) Colour Sash colour Handle Casement locking Friction stay Viewed from Open in/out Reinforcing rule Reinforcing type Tran/Mull joints Vector Excluder <b>WER RATING</b>	B35 75mm T Sash B35 75mm T Sash B35 75mm T Sash B35 75mm T Sash No drip bar No add-on No add-on No add-on No add-on No ventilator No ventilator No ventilator No ventilator White White White Cranked Espag Handle Maco MK3 Shootbolt Locking Standard Stay Viewed from outside Open out Bay Reinforcing Steel Reinforcing Welded joint Vector Excluder <b>A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		


<b>4</b>	Elite 70 Ovolo Casement	Bay 4 of 5
O/A Sizes 435mm x 1650mm (Style 2)		<b>Specification</b>
	Transom	B20/21 66mm T/Z Section
	Frame drip bar Add-on (Head) Add-on (Cill) Add-on (Left jamb) Add-on (Right jamb) Ventilator (Head) Ventilator (Glass) Ventilator (Frame) Colour Viewed from Reinforcing rule Reinforcing type Tran/Mull joints <b>WER RATING</b>	No drip bar No add-on No add-on No add-on No add-on No ventilator No ventilator No ventilator White Viewed from outside Bay Reinforcing Steel Reinforcing Welded joint <b>A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		


<b>5</b>	Elite 70 Ovolo Casement	Bay 5 of 5
O/A Sizes 495mm x 1650mm (Style 9)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Handle White Cranked Espag Handle Casement locking Std Mushroom Locking Friction stay Egress Stay Viewed from Viewed from outside Open in/out Open out Reinforcing rule Bay Reinforcing Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		

<b>6</b>	Elite 70 Ovolo Casement	
O/A Sizes 1800mm x 1700mm (Style 33)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Mullion B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Cill colour White Handle White Cranked Espag Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Egress Stay Viewed from Viewed from outside Open in/out Open out <b>Reinforcing type Thermal Reinforcing</b> Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>
<b>Aperture Options</b>		
Ventilator (Sash)	No ventilator (H4)	Friction stay Standard Stay (H1)
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 H1 H4		
Notes :		

<b>7</b>	Elite 70 Ovolo Casement	
O/A Sizes 1800mm x 1200mm (Style 75)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Mullion B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Cill colour White Handle White Cranked Espaq Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Standard Stay Viewed from Viewed from outside Open in/out Open out <b>Reinforcing type Thermal Reinforcing</b> Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A6 D1 H1		
Notes :		


<b>8</b>	Elite 70 Ovolo Casement	
O/A Sizes 1130mm x 1210mm (Style 6)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Cill colour White Handle White Cranked Espaq Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Standard Stay Viewed from Viewed from outside Open in/out Open out <b>Reinforcing type Thermal Reinforcing</b> Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		


<b>9</b>	Elite 70 Ovolo Casement	
O/A Sizes 1500mm x 1200mm (Style 46)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Mullion B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Cill colour White Handle White Cranked Espag Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Standard Stay Viewed from Viewed from outside Open in/out Open out <b>Reinforcing type Thermal Reinforcing</b> Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4 F1		
Notes :		


<b>10</b>	Elite 70 Ovolo Single Door	
O/A Sizes 870mm x 2060mm (Style 2)		<b>Specification</b>
		Threshold PVCu Threshold Midrail B24 110mm T Section Sash B45/46 110mm T/Z Sash Frame drip bar No drip bar Sash drip bar B86 Drip Bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) No ventilator Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Cill colour White Handle White lever/lever Door lock Paddock Door Lock Viewed from Viewed from outside Open in/out Open in Reinforcing rule Fully Reinforced Reinforcing type Steel Reinforcing Midrail joints Welded joint WER RATING 1.6 Centre Pane U-Value
<b>Glazing Details &amp; Apertures</b>		<b>Panel Details &amp; Apertures</b>
4-16-4-16-4 Obscure Tough Low E : 16mm SWISS SPACER V * TBA *		*Argon
Gas Filled *		Half Panel 28mm / Manor Half / Solid / White (Spectus) C130 / 8mm MDF / Cut to Size (V) /
A1		A7 -
Notes :		

<b>11</b>	Elite 70 Ovolo Casement	
O/A Sizes 1150mm x 1210mm (Style 6)		<b>Specification</b>
	Transom B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Cill colour White Handle White Cranked Espaq Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Standard Stay Viewed from Viewed from outside Open in/out Open out <b>Reinforcing type Thermal Reinforcing</b> Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>	
	<b>Glazing Details &amp; Apertures</b> 4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled * A1 A4	
Notes :		

<b>12</b>	Elite 70 Ovolo Casement	
O/A Sizes 1680mm x 1360mm (Style 33)		<b>Specification</b>
	Transom B20/21 66mm T/Z Section Mullion B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Cill colour White Handle White Cranked Espaq Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Egress Stay Viewed from Viewed from outside Open in/out Open out <b>Reinforcing type Thermal Reinforcing</b> Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>	
	<b>Aperture Options</b> Ventilator (Sash) No ventilator (H4) Friction stay Standard Stay (H1)	
<b>Glazing Details &amp; Apertures</b> 4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled * A1 H1 H4		
Notes :		

<b>13</b>	Elite 70 Ovolo Casement	
O/A Sizes 595mm x 1000mm (Style 1)		<b>Specification</b>
		Frame drip bar No drip bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Cill colour White Viewed from Viewed from outside Reinforcing type Steel Reinforcing <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1		
Notes :		

<b>14</b>	Elite 70 Ovolo Casement	
O/A Sizes 1140mm x 1360mm (Style 33 [R		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Mullion B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Cill colour White Handle White Cranked Espaq Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Egress Stay Viewed from Viewed from outside Open in/out Open out <b>Reinforcing type Thermal Reinforcing</b> Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>
<b>Aperture Options</b>		
Ventilator (Sash) No ventilator (A4) Friction stay Standard Stay (A1)		
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4 D1		
Notes :		


	Elite 70 Ovolo Bay Layout	
		<b>Specification</b>
		Cill C225 225mm Classic Nose Cill Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Pole B70 Bay Pole (Elite 70) Colour White Sash colour White Addon colour White Cill colour White Viewed from Viewed from outside Reinforcing rule Bay Reinforcing Reinforcing type Steel Reinforcing
Notes :		


<b>15</b>	Elite 70 Ovolo Casement	Bay 1 of 5
O/A Sizes 495mm x 1490mm (Style 8)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Handle White Cranked Espag Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Egress Stay Viewed from Viewed from outside Open in/out Open out Reinforcing rule Bay Reinforcing Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		


<b>16</b>	Elite 70 Ovolo Casement	Bay 2 of 5
O/A Sizes 435mm x 1490mm (Style 2)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Frame drip bar No drip bar Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Viewed from Viewed from outside Reinforcing rule Bay Reinforcing Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		


<b>17</b>	Elite 70 Ovolo Casement	Bay 3 of 5
O/A Sizes 435mm x 1490mm (Style 6)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) No ventilator Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Handle White Cranked Espag Handle Casement locking Maco MK3 Shootbolt Locking Friction stay Standard Stay Viewed from Viewed from outside Open in/out Open out Reinforcing rule Bay Reinforcing Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint Vector Excluder Vector Excluder <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		

<b>18</b>	Elite 70 Ovolo Casement	Bay 4 of 5
O/A Sizes 435mm x 1490mm (Style 2)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Frame drip bar No drip bar Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Viewed from Viewed from outside Reinforcing rule Bay Reinforcing Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		

<b>19</b>	Elite 70 Ovolo Casement	Bay 5 of 5
O/A Sizes 495mm x 1490mm (Style 9)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Sash (Head) B35 75mm T Sash Sash (Cill) B35 75mm T Sash Sash (Left jamb) B35 75mm T Sash Sash (Right jamb) B35 75mm T Sash Frame drip bar No drip bar Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) 5000 SIMON VENT Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Sash colour White Handle White Cranked Espag Handle Casement locking Std Mushroom Locking Friction stay Egress Stay Viewed from Viewed from outside Open in/out Open out Reinforcing rule Bay Reinforcing Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Clear Tough Low E : 12mm Thermal Spacer *Argon Gas Filled *		
A1 A4		
Notes :		

<b>20</b>	Elite 70 Ovolo Casement	
O/A Sizes 285mm x 2470mm (Style 2)		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Frame drip bar No drip bar Cill No cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) SWR748S 3mm Coupler Ventilator (Head) No ventilator Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Addon colour White Viewed from Viewed from outside Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Obscure Tough Low E : 12mm Thermal Spacer Satin Tough		
*Argon Gas Filled *		
A1 A4		
Notes :		

<b>21</b>	CD70 Composite Door	
O/A Sizes 950mm x 2500mm (Style 12)		<b>Specification</b>
		Sash Straight Edge Slab Sash drip bar 2537 Mill Drip Bar Cill C225 225mm Classic Nose Cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) No add-on Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Sash) No ventilator Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Cill colour White Handle 9904 Offset Bar Handle 1200 Door lock Composite Door Lock Open in/out Open in Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint
<b>Glazing Details &amp; Apertures</b>		<b>Panel Details &amp; Apertures</b>
4-16-4-16-4 Obscure Tough Low E : 16mm SWISS SPACER V Satin Tough		Infinity Collection / GD03 Infinity 03 / Solid / Anthracite Grey / White / / /
*Argon Gas Filled *		A4 -
A1		
Notes :		

<b>22</b>	Elite 70 Ovolo Casement	
O/A Sizes 285mm x 2470mm (Style 2 [Rev		<b>Specification</b>
		Transom B20/21 66mm T/Z Section Frame drip bar No drip bar Cill No cill Add-on (Head) No add-on Add-on (Cill) No add-on Add-on (Left jamb) SWR748S 3mm Coupler Add-on (Right jamb) No add-on Ventilator (Head) No ventilator Ventilator (Glass) No ventilator Ventilator (Frame) No ventilator Colour White Addon colour White Viewed from Viewed from outside Reinforcing type Steel Reinforcing Tran/Mull joints Welded joint <b>WER RATING A RATED</b>
<b>Glazing Details &amp; Apertures</b>		
4-12-4-12-4 Obscure Tough Low E : 12mm Thermal Spacer Satin Tough *Argon Gas Filled * A1 A4		
Notes :		

Glass & Panel Description	Location	Gross	Disc.	Nett
---------------------------	----------	-------	-------	------

Sub Totals

Extra Items	Gross	Disc.	Nett
1 off SUPPLY & INSTALL	£0.00		£0.00
Sub Totals	£0.00		£0.00

Total	£8,601.75
VAT @ 20.00%	£1,720.35
Total (Incl. VAT)	£10,322.10